

NEW

minilec[®]
a trusted name for 40 years

Advantageous. Sleek. Brighter. Smarter.
MICROWARN 0600 series Annunciators Replaces Older Series MICROWARN 9600



Weights Only
800 gm

Minilec (India) Pvt. Ltd

1073 /1-2-3 A Post Pirangut, Mutha Rd.
Taluka, Mulshi, District -Pune PIN 412 111
(India) Plove: 91-20-22922365-66-67 Fax: 91-20-22922134

CLICK HERE
mkt1@minilecgroup.com

Minilec upgrades its MICROWARN series Annunciator Highlights -

Depth is Reduced by 73 mm: Now the depth of New MICROWARN 0600 Annunciator is 80mm instead of 153 mm.

Selectable NO/NC & Trip & Non Trip Grouping: Now you can select both NO /NC configuration as well as Trip & Non trip Grouping of faults.

3 Relay Outputs: For TRIP / NON-TRIP Group Hooters & one Programmed for Self Supervision for CPU failure.

Optionally one contact can be reprogrammed on request **at cost** for use as DC Fail annunciation or for using it for Ring back Hooter when Trip & Non-Trip Grouping facility is provided or for use as common Master Alarm Contact. Presently this intelligence is not available.

Wide band Auxiliary Supply: This wide band Voltage supply 90 -270 V AC-DC comes as a default feature in new MICROWARN. Earlier it was optional.

SMPS Watch Dog Indication: This LED remains ON indicating the healthiness of the Power Supply.



Ultra Bright Multi LED:
GREEN / RED / AMBER Color



5.08 pitch Terminals:
Internationally acceptable Terminals.



EM No: E M M/VN 0600