

# ELECTRONIC HOOTER

## F3 MEH1



### Technical Specifications

Aux. Supply	24V AC / DC, 48V AC / DC, 90-270V AC / DC
Frequency	48 to 63 Hz in case of VAC model
Power consumption	20 VA max.
Standard sound output	90 to 115 db at 30cm
Tone	Three different selectable tones
Volume level adjustment	Continuous adjustable by means of built-in Potentiometer
Indication	Power on 3mm red LED
Mounting Type	Panel Mounting & Wall Mounting
Operating Temperature	0 to +60°C
Humidity	Up to 95% RH Non-condensing
Enclosure	ABS molded enclosure
Unit Dimensions Overall (mm) (L x W x D) Cut out (L x W)	96 x 96 x 82 92 x 92
Unit Weight (gms.) Appx.	400gm

**Our Other Products: Phase Failure Relays, Motor/Pump Protection relays, Monitoring Relays, Electronic Timers, Liquid Level Controllers, Power Line Transducers & Multifunction Meter, Automation Products, Alarm Annunciators, Soft Starters, AC Drives, PCB, and Products for Agri Sector.**



## Minilec (India) Pvt. Ltd.



S.No. 1073/1-2-3, At Post : Pirangoot, Tal : Mulshi, Dist : Pune (India), Pin : 412 111  
 Tel : (020) 67920100 / 22922354-57. Fax : (020) 22922134 or (020) 25432349 / 25431573.  
 Website : <http://www.minilecgroup.com> E-Mail : [mkt1@minilecgroup.com](mailto:mkt1@minilecgroup.com)